



Liquid Wallpaper Remover

For the easy removal of normal wallpapers, distemper and smear-resistant emulsion paint.

Scope of application:	Appropriate for the easy removal of normal wallpapers, glue-bound distemper and smear-resistant emulsion paint. Also applicable for textile wallpapers.
Properties:	Effortlessly removes all types of wallpapers and glue-bound distempers; the product can be applied with the garden irrigation nozzle; high potency of active ingredients = low consumption;
Technical specification:	Raw material base: aqueous solution of surfactants and alcohol; Make-up ratio: 250 ml to 5-6 l water; Consumption: 250 ml for 50 - 100 m ² .
Processing:	In case of wallpapers that are difficult to remove proceed as follows: Stir 250 ml of Liquid Wallpaper Remover into 5 to 6 l warm water. For other wallpapers, stir 250 ml of Liquid Wallpaper Remover into 10 l warm water. Apply the Liquid Wallpaper Remover generously with a ceiling brush, sponge or garden irrigation nozzle in the running direction of the wallpaper, and allow it to react for approx. 10 to 15 minutes. Repeat the application, if required. Then remove the wallpapers strip by strip. Always clean the tools thoroughly with water immediately after use.
Identification:	Please refer to the EC safety data sheet for the pertinent information.
Storage property:	Store the product in a cool, dark and dry place.
Other:	Always read the label and product information before use. Use warm or hot water to increase the effect. Water-repellent wallpapers must be roughened with a spiked roller before applying the liquid.
Container sizes:	Bottle with 250 ml Bottle with 500 ml Bottle with 1,000 ml Jerrican with 5 l